

Model: Model S

Vehicle System: 00 - Inspection & Service

Region: All

Tech Note: Model S Annual Service

Tech Notes are internal announcements that help to communicate and track new information about Tesla Service concerns.

Date: _____ Odometer Value: _____
VIN: _____ Service Technician: _____

Fill out the column for the annual check being performed. Blacked-out cells are not required for that year's inspection.

The specified operations repeat after year 5. For example, perform Year 1 operations in year 6, and Year 2 operations in year 7.

Actions: V (visual inspection) F (functional check) T (torque check) E (electronic check) CL (clean/lubricate) R (replace)

Component	Action	Year 1 12,500 mi 20,000 km	Year 2 25,000 mi 40,000 km	Year 3 37,500 mi 60,000 km	Year 4 50,000 mi 80,000 km	Year 5 62,500 mi 100,000 km
Brake Fluid	R		<input type="checkbox"/>		<input type="checkbox"/>	
Coolant	R				<input type="checkbox"/>	
Transmission Fluid	R	Every 12 years / 150,000 mi / 240,000 km				
Panoramic roof, if equipped	F, CL	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Wiper blades	R	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Windshield washer (top off fluid)	F	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Doors, hood, and liftgate	V,F	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Seat belts	V,F	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
RKE/passive entry	F	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Replace key fob battery	R	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Horn, interior/exterior lighting	V,F	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Charge port	V,F	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Check for active and historical alerts, repair any issues found, clear alerts	V,F	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Cabin air filter	R	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
A/C desiccant bag	R		<input type="checkbox"/>		<input type="checkbox"/>	
Coolant level	V	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Radiator/condenser (clear debris if more than 10% blocked)	V	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Tire rotation		Every 5,000 mi / 8,000 km				
Record tread depth, FR (replace if 3/32" / 2 mm or less)	V	Outer Center Inner	Outer Center Inner	Outer Center Inner	Outer Center Inner	Outer Center Inner
Record tread depth, FL (replace if 3/32" / 2 mm or less)	V	Outer Center Inner	Outer Center Inner	Outer Center Inner	Outer Center Inner	Outer Center Inner
Record tread depth, RR (replace if 3/32" / 2 mm or less)	V	Outer Center Inner	Outer Center Inner	Outer Center Inner	Outer Center Inner	Outer Center Inner

		Outer Center Inner	Outer Center Inner	Outer Center Inner	Outer Center Inner	Outer Center Inner
Record tread depth, RL (replace if 3/32" / 2 mm or less)	V					
Set tire pressure, FR	V					
Set tire pressure, FL	V					
Set tire pressure, RR	V					
Set tire pressure, RL	V					
Record brake pad thickness, FR (replace if 2 mm or less)	V					
Record brake pad thickness, FL (replace if 2 mm or less)	V					
Record brake pad thickness, RR (replace if 2 mm or less)	V					
Record brake pad thickness, RL (replace if 2 mm or less)	V					
Park brake pads: record thickness	V					
Brake fluid level, pipes, and hoses	V	<input type="checkbox"/>				
Battery enclosure	V	<input type="checkbox"/>				
Coolant leaks	V	<input type="checkbox"/>				
Rear subframe components, drive unit	V	<input type="checkbox"/>				
Suspension	V	<input type="checkbox"/>				
Suspension bolts	T	<input type="checkbox"/>				
Steering gear	T					<input type="checkbox"/>
Secondary hood release latch	CL	<input type="checkbox"/>				
Alignment	F	<input type="checkbox"/>				
Verify normal vehicle operation	F	<input type="checkbox"/>				

SERVICE NOTES:

For feedback on the accuracy of this document, email ServiceBulletinFeedback@teslamotors.com.